



## FenomPro™ Specifications [900-0005 US]

Specification	Description
<i>Dimensions and weight</i>	Height: 145 mm, Width: 230 mm, Depth: 140 mm Weight (including handpiece): 2.4 kg
<i>Electrical data</i>	Device power consumption: < 20 VA Power supply mains voltage: 100–240 V ~50-60 Hz
<i>Operating Range</i>	Ambient temperature between 15-30°C (59-86°F) Relative humidity between 20-80% Ambient pressure between 80-106 kPa
<i>Measurement range</i>	10 ppb to 200 ppb
<i>Measurement time</i>	Results will display in 28 seconds
<i>Precision</i>	< 5 ppb or 10% of concentration
<i>Accuracy</i>	±5 ppb or ±10% of concentration
<i>Limit of detection</i>	10 ppb
<i>Exhalation parameters</i>	Exhalation time: 10 seconds Exhalation pressure is between 15-25 cm-water Exhalation flow rate is between 45-55 mL/s
<i>Rechargeable battery</i>	Capacity: > 15 tests over 6 hours on a fully charged battery Charging time: 4 hours
<i>Device life and service</i>	Fenom Pro™ device life is 5 years. Periodic service by your local representative is required.
<i>Manufacturer information</i>	Spirosure, Inc. 7020 Koll Center Parkway, Suite 110, Pleasanton, CA 94566-3107 info@spirosure.com

For more information or to order, visit <http://fenomasthma.com>.